



Shock Metal Bath TRSM-601

www.labdel.com | info@labdel.com

Shock Metal Bath TRSM-601

Shock Metal Bath TRSM-601 has a licensed module clamping and squeezing strategy with a temperature range of 15 to 110 °C. It has a 2000-rpm mixing movement, an adequately mixing impact, and a quicker speed. It used to help program altering and capacity, and it could hold an assortment of modules. The activity of warming, cooling, and blending is illustrated.

Features:

2000 rpm ultra-high-speed mixing, further developed blending impact and quicker speed

Wide temperature adjustment range (15 to 110 °C)

The greatest temperature precision (20 to 45 °C) is 0.5 °C

It can convey an assortment of modules

Aid the altering and capacity of assignments

The temperature correction method is simpler and more convenient

Protected clasping and squeezing strategy for modules

Specifications :

Dimensions L×W×H	186×267×145 mm
Display	LCD
Input Voltage	100 to 120V/220 to 240V, 50Hz/60Hz
Maximum Cooling Rate	5 °/min
Maximum Heating Rate	5.5 °/min
Mixing Diameter	3 mm
Power	200 W
Programming	9
Temperature Control Accuracy [20 To 45°]	± 0.5 °
Temperature Control Range	100 °
Temperature Range	15 ° / 100 °
Temperature Uniformity [20 To 45°]	± 0.5 °
Time Setting Range	1min to 99 h 59 min
Working Environment Humidity	0.8
Working Environment Temperature	5 to 40 °
Speed Adjustment Range	200 to 2000 rpm



Email: info@labdel.com | Website: www.labdel.com