



Vertical Air Laminar Flow Cabinet TRVLC-604

www.labdel.com | info@labdel.com

Vertical Air Laminar Flow Cabinet TRVLC-604

Vertical Air Laminar Flow Cabinet TRVLC-604 is equipped with a wind volume adjustable fan system, with an average wind speed of 0.25 to 0.45 m/s. It has a double - single dimension. It has a HEPA filter as well as a primary filter. With a stainless steel work area and a glass sliding door. Consumption of maximum power of 800 W. A digital display panel with a crystal liquid interface controls the system. It comes with a power outlet.

Features:

The vertical closed worktop effectively prevents outside gas from entering and the weird odor

It employs a wind volume adjustable fan system

A light-touch type switch and a dual-speed voltage regulation device to maintain a suitable wind speed in the working area

The personalized design takes into account all of the user's requirements

It uses a spring-type sliding door that can be oriented in the desired position

It is designed to be operated easily

The front cover can be easily accessible to swap screens and electrical equipment

The work area made with a stainless steel

Having a digital display operates with a liquid crystal interface

Specifications :

Dimension Of Working Area(W1×D1×H1)	1370×650×580 mm
Half Ventilation Peak Value	? 3?m(XYZ direction)
Illumination	?300LX
Maximum Power Consumption	800 W
Noise	?62dB
Number Of Bacteria	?0.5per utensil. Hour (90mm utensil)
Overall Dimension (W×D×H)	1530×690×1600mm
Power Supply	AC, 220 V/50Hz
Specification And Number Of A Fluorescent Lamp Or UV Lamps Of Ultraviolet Lights	8W×2/10 W×2
Suited Number	Double-single
The Average Wind Speed	0.25 to 0.45m/s



Email: info@labdel.com | Website: www.labdel.com